

RA26

VHF 88 Channels 5W IP67 Floats Flashes-alarm NOAA Marine Transceiver (USA/INT/CAN)

Main Functions:

- Buoyant, Stylish and Easy to Use, Slim, lightweight, High Performance
- USB charging(Micro-B USB type)
- IPX7 Waterproof Construction(1m depth of water for 30 minutes)
- Floats and Flashes Alarm
- Vibration Draining Function
- 11 Hours of Battery Life, 4-step Battery Life Indicator
- Dual/Tri-watch Functions
- Monitor Function Opens Noise Squelch
- Auto Scan Function
- LCD Auto Backlighting
- Emergency switch 16/9 channel
- Fast charging
- High/low power switching



RA26

VHF 88 Channels 5W IP67 Floats Flashes-alarm NOAA Marine Transceiver (USA/INT/CAN)

General Specifications:

General

Frequency Range:	TX: 156.000~161.450MHz RX: 156.000~163.425MHz
Modulation:	FM (16K0G3E)
Battery Pack:	DC3.7V, 1500mAh li-ion
Frequency Stability:	±10ppm
Operating Temperature:	-15°C~+55°C
Dimensions (W×H×D):	140mm×64mm×35mm
Weight:	220g (With battery, antenna and belt clip)

Receiver

Receive Sensitivity:	≤0.22 μV
Squelch Sensitivity:	≤0.22 μV
HUM and Noise :	≥40 dB
Adjacent Channel Selectivity:	≥70 dB
Spurious Response:	≥70 dB
Intermodulation Rejection Ratio:	≥68 dB
Audio Output Power:	≥0.6 W (10%)

Transmitter

Current Drain:	≤1.5A(High power) ≤0.9A(Low power) ≤0.35A(Max .audio output)
Max. Frequency Deviation:	±5 kHz
Spurious Emissions:	≤0.25uw
Adjacent Channel Power:	≥70 dB
Audio Harmonic Distortion:	≤10 %
Output Power:	5 W \ 1W

Package Includes:

- 1 x Marine Transceiver
- 1 x USB Adaptor
- 1 x Antenna
- 1 x User manual
- 1 x Belt Clip
- 1 x Hand strap

CE FC RoHS 

Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA