

RETCVIS RT55

- Water-resistant Protection: IP67
- Floats on Water: the transceiver can be floated when fell into water

- Vibration Water Draining Function
- Dual-Watch/Tri-Watch



RT55 IP67 VHF Marine Transceiver

Main functions:

- Adjustable volume
- Adjustable Squelch
- Lock Function
- Scan Function
- Channel Group Selective
- Monitor Function
- Call Channel Programming
- Channel Selection: Channel 16/Call Channel/Weather Channels
- Volume Mute Function
- Automatic Backlight
- Power Save Function

General Specification:

Frequency Range	TX: 156.000-161.450MHz RX: 156.050-163.425MHz
Type of Emission	FM(16K0G3E)
Frequency Stability	±10PPM
Battery Pack	1200mAh Li-ion (DC7.4V)
Operating Temperature Range	-20°C~+55°C
Antenna Impedance	50
Dimensions (H x W x D)	140mm x 65mm x41mm
Weight	288g(With battery,antenna,belt clip)

Transmitter Specification:

Output Power	5W/1W
Maximum Frequency Deviation	±5kHz
Spurious Emission	0.25μW
Adjacent Channel Power	≥70dB
Audio Harmonic Distortion	≤10%
Current Drain	≤1.5A(High power)
	≤0.9A(Low power)
	≤0.35A(Max audio output)

Receiver:

Receiver Sensitivity	≤0.22μV
Squelch Sensitivity	≤0.22μV
HUM and Noise	≥40dB
Adjacent Channel Selectivity	≥70dB
Spurious Response	≥70dB
Intermodulation Rejection	≥68dB
Audio Output Power	≥0.5W(10%)

Package includes:

- 1 x Antenna
- 1 x Sling
- 1 x Battery Pack
- 1 x Power Adapter
- 1 x Charger
- 1 x Belt Clip
- 4 x Screw
- 1 x User Manual
- 1 x RT55 Marine two way radio



Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA